



## LUXOUS 1147 H2no FR

### Product information

Application	Inside
System	Hanging, Sliding
Feature	Energy saving
Flame retardant	Yes
Material	Polyester 100%
Pattern	Full transparent
Warranty	Warranty five (5) years under all types of greenhouse covering. See Svensson's limited warranty for all terms, conditions and exclusions in writing.

Properties	Value	Unit	Test Methods
Shading level in diffused light PAR**	25	%	Protocol NEN 2675
	19	%	Svensson method
Shading level in direct light PAR**	15	%	Protocol NEN 2675
	11	%	Svensson method
UV light transmission ***	12	%	Svensson method
Energy saving	47	%	Svensson method
Width of strips	4	mm	
Weight	57	g/m <sup>2</sup>	

\* Width 50 mm

\*\* PAR = 400 - 700 nm, accuracy +/- 1%

\*\*\* UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy.

Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and names are protected by patent and other intellectual property rights.

Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant.

AB Ludvig Svensson is an ISO 14001/90001 certified company.