





## **Xsect X-air**

## **Product information**

Application Exterior, Inside
System Roof/wall
Feature Insect control

Flame retardant No

Material Polyolefin 100%

Insect exclusion Moderate exclusion of thrips and insects of similar sizes. Measured in

collaboration with Instituto Entoma.

Properties	Value	Unit	Test Methods
Shading level in diffused light PAR**	21	%	Protocol NEN 2675
Shading level in direct light PAR**	9	%	Protocol NEN 2675
Weight	97	g/m²	
Porosity	35	%	According to Svensson
Warp density	33	yarns/cm	
Weft density	21	yarns/cm	

<sup>\*</sup> Width 50 mm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy.

Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and names are protected by patent and other intellectual property rights.

Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant.

AB Ludvig Svensson is an ISO 14001/90001 certified company.

<sup>\*\*</sup> PAR = 400 - 700 nm, accuracy +/- 1%

<sup>\*\*\*</sup> UV-light = 300 - 400 nm